



DONNEES TECHNIQUES - LAVE-BATTERIE LP31-LP38

MODÈLE	LP31-dy	LP31-dy-CV	LP31/L-dy	LP31/L-dy-CV	LP38-dy	LP38-dy-CV	LP38/L-dy	LP38/L-dy-CV	
CODE	LA00025	LA00043	LA00028	LA00044	LA00026	LA00046	LA00226	LA00045	
DIMENSIONS l x p x h	1535x965x1835	1530x1080x2050	1535x965x1835	1530x1080x2050	1535x965x2035	1530x1080x2250	1535x965x2035	1530x1080x2250	mm
DEBIT/H casiers/H	30/15/8	30/15/8	30/15/8	30/15/8	30/15/8	30/15/8	30/15/8	30/15/8	Nr.
DUREE DU CYCLE	2'-4'-7'	2'-4'-7'	2'-4'-7'	2'-4'-7'	2'-4'-7'	2'-4'-7'	2'-4'-7'	2'-4'-7'	Min.
DIMENSIONS CASIER	1350x700	1350x700	1350x700	1350x700	1350x700	1350x700	1350x700	1350x700	mm
HAUTEUR DU PLAN DE TRAVAIL	865	865	865	865	865	865	865	865	mm
OUVERTURE DE CHARGEMENT	640	640	640	640	840	840	840	840	mm
TENSION D'ALIMENTATION	400 V3/N~50Hz	400 V3/N~50Hz	400 V3/N~50Hz	400 V3/N~50Hz	400 V3/N~50Hz	400 V3/N~50Hz	400 V3/N~50Hz	400 V3/N~50Hz	V
ELECTROPOMPE LAVAGE	4x1500	4x1500	2x3000	2x3000	4x1500	4x1500	2x3000	2x3000	W
ELECTROPOMPE RINÇAGE	550	550	550	550	550	550	550	550	W
RESISTANCE CUVE (électrique)	9000	9000	9000	9000	9000	9000	9000	9000	W
(vapeur)	10	10	10	10	10	10	10	10	kg/V
RESISTANCE SURCHAUFFEUR (électr.)	2x6000	2x6000	2x6000	2x6000	2x6000	2x6000	2x6000	2x6000	W
(vapeur)	30	30	30	30	30	30	30	30	kg/V
PUISSANCE NOMINALE (électrique)	18000	18000	18000	18000	18000	18000	18000	18000	W
(vapeur)	40/8950	40/8950	40/8950	40/8950	40/8950	40/8950	40/8950	40/8950	kg/W
INTENSITE MAXIMALE	38	38	38	38	38	38	38	38	A
CAPACITE DE LA CUVE	177	177	177	177	177	177	177	177	Lt
CAPACITE DU SURCHAUFFEUR	2x8	2x8	2x8	2x8	2x8	2x8	2x8	2x8	Lt
ALIMENTATION EAU	50 ÷ 55	12 ÷ 15	50 ÷ 55	12 ÷ 15	50 ÷ 55	12 ÷ 15	50 ÷ 55	12 ÷ 15	°C
CONSOMMATION EAU PAR CYCLE	12	12	12	12	12	12	12	12	l
CONSOMMATION EAU ORAIRE	240-144-96	240-144-96	240-144-96	240-144-96	240-144-96	240-144-96	240-144-96	240-144-96	l
PRESSION EAU	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	Bar
PRESSION VAPEUR	0,5 ÷ 2	0,5 ÷ 2	0,5 ÷ 2	0,5 ÷ 2	0,5 ÷ 2	0,5 ÷ 2	0,5 ÷ 2	0,5 ÷ 2	Bar
DURETE DE L'EAU	5 ÷ 10	5 ÷ 10	5 ÷ 10	5 ÷ 10	5 ÷ 10	5 ÷ 10	5 ÷ 10	5 ÷ 10	°F
TEMPERATURE EAU RINÇAGE	80 ÷ 90	80 ÷ 90	80 ÷ 90	80 ÷ 90	80 ÷ 90	80 ÷ 90	80 ÷ 90	80 ÷ 90	°C
RACCORD ENTREE' DE L'EAU	1"	1"	1"	1"	1"	1"	1"	1"	"G
EVACUATION EAU	1"1/2	1"1/2	1"1/2	1"1/2	1"1/2	1"1/2	1"1/2	1"1/2	"G
POIDS NET	390	450	380	440	420	480	410	470	kg
POIDS LOURD	510	600	500	590	540	630	530	620	kg
DIMENSIONS EMBALLAGE	1700x1200x2200	1700x1200x2350	1700x1200x2200	1700x1200x2350	1700x1200x2400	1700x1200x2550	1700x1200x2400	1700x1200x2550	mm
NIVEAU DU BRUIT	<70	<70	<70	<70	<70	<70	<70	<70	dB(A)
POMPE LAVAGE AUTOVIDANGEABLE	si	si	si	si	si	si	si	si	
ACCESSOIRES									
POMPE DE VIDANGE	30	30	30	30		30		30	W