

MOD.P440-ek / P440-CV				P440-ek	P440-CV	
I	F	GB	D			
DATI TECNICI	DONNEES TECHNIQUES	SPECIFICATIONS	TECHNISCHE DATEN			
DIMENSIONI l x p x h	DIMENSIONS l x p x h	DIMENSIONS l x w x h	ABMESSUNGEN LxTxH	600x705x1425	600x705x1710	mm
CAPACITA' ORARIA cestelli/ora	DEBIT/H casiers/H	WASHING CAPACITY baskets/H	STUNDENLEISTUNG Körbe/Stunde	30/20/15 60/30/20	30/20/15 60/30/20	Nr.
CAPACITA' ORARIA piatti/ora	DEBIT/H assiettes/H	WASHING CAPACITY dishes/H	STUNDENLEISTUNG Teller/Stunde	720/480/360 1440/720/480	720/480/360 1440/720/480	Nr.
DURATA CICLO	DUREE DU CYCLE	WASH CYCLE	PROGRAMMDAUER SEL.	2÷3÷4 1÷2÷3	2÷3÷4 1÷2÷3	MIN.
DIMENSIONI UTILI DI LAVAGGIO	DIMENSIONS UTILES DE LAVAGE	WASHING AREA DIMENSIONS	MAXIMALE DURCHGANGHÖHE	500x600x440H	500x600x440H	mm
DIMENSIONI CESTELLO	DIMENSIONS CASIER	BASKET SIZE	KORBAMAßE	60 x 50	60 x 50	cm
NUM.PIATTI /CESTELLO	NUM.ASSIETTES POUR CASIER	PLATES PER BASKETS	N°.TELLER PRO KORB	24	24	Nr.
ALTEZZA PIANO DI LAVORO	HAUTEUR DU PLAN DE TRAVAIL	WORK HEIGHT	ARBEITSOBERFLÄCHENHÖHE	860	860	mm
TENSIONE D'ALIMENTAZIONE	TENSION D'ALIMENTATION	VOLTAGE	VERSORGUNGSPANNUNG	400 V3N~50Hz	400 V3N~50Hz	V
ELETTROPOMPA	ELECTROPOMPE	ELECTRIC PUMP	PUMPENMOTOR	900	900	W
ELETTROPOMPA DI RISCIAQUO	ELECTROPOMPE RINÇAGE	RINSING ELECTRIC PUMP	NASCHSPÜLPUMPENMOTOR	385	385	W
RESISTENZA VASCA	RESISTANCE CUVE	WASH TANK ELEMENTS	TANKHEIZUNG	2000	2000	W
RESISTENZA BOILER	RESISTANCE SURCHAUFFEUR	RINSE TANK ELEMENTS	BOILERHEIZUNG	6000	4500	W
POTENZA NOMINALE	PUISSANCE NOMINALE	TOTAL RATING	GESAMTVERBRAUCH	6900	5400	W
INTENSITA' DI CORR.MAX	INTENSITE MAXIMALE	MAX CURRENT INTENSITY	MAXIMALE STROMAUFNAHME	12	12	A
CAPACITA' VASCA	CAPACITE DE LA CUVE	TANK CAPACITY	TANKFÜLLUNG	34	34	Lt
CAPACITA' BOILER	CAPACITE DU SURCHAUFFEUR	BOILER CAPACITY	BOILERINHALT	8	8	Lt
DOSATORE RISCIAQUO	DOSEUR DE PRODUIT DE RINÇAGE	RINSE AID DISPENSER	NACHSPÜLMITTELDOSIERANLAGE	si-oui-yes-ja	si-oui-yes-ja	
ALLACCIAMENTO ACQUA	ALIMENTATION EAU	WATER CONNECTION	WASSERANSCHLUß	45 ÷ 55	10 ÷ 12	°C
PORTATA ACQUA POMPA	DEBIT EAU MOTEUR	PUMP DELIVERY	UMWALZUNG WASCHPUMPE	420	420	l./min
CONSUMO ACQUA PER CICLO	CONSOMMATION EAU PAR CYCLE	CYCLE WATER CONSUMPTION	WASSERVERBRAUCH - ZYKLUS	3,2	3,2	l
PRESSIONE ACQUA	PRESSION EAU	WATER PRESSURE	WASSERDRUCK	2 ÷ 4	2 ÷ 4	Bar
DUREZZA CONSIGLIATA DELL'ACQUA	DURETE DE L'EAU	WATER HARDNESS	EMPFOHLENE WASSERHÄRTE	5 ÷ 10	5 ÷ 10	°F
TEMPERATURA ACQUA RISCIAQUO	TEMPERATURE EAU RINÇAGE	RINSING WATER TEMPERATURE	SPÜLWASSERTEMPERATUR	80 ÷ 90	80 ÷ 90	°C
RACCORDO ENTRATA ACQUA	RACCORDEMENT EAU	WATER INLET	WASSEREINLAUFROHRWEITE	3/4"	3/4"	"G
RACCORDO SCARICO ACQUA	EVACUATION EAU	WATER OUTLET	WASSERABLAUFROHRWEITE	32 mm - 1"1/4	32 mm - 1"1/4	"G
PESO NETTO	POIDS NET	NET WEIGHT	NETTOGEWICHT	107	132	kg
PESO LORDO	POIDS LOURD	GROSS WEIGHT	BRUTTOGEWICHT	125	150	kg
DIMENSIONI IMBALLO	DIMENSIONS EMBALLAGE	PACKING DIMENSIONS	VERPACKUNGABMESSUNGEN	730x860x1500	730x860x1700	mm
RUMOROSITA'	NIVEAU DU BRUIT	NOISE	GERÄUSCH	<65	<65	dB(A)
DOTAZIONI OPTIONAL	ACCESSOIRES	OPTIONAL	OPTIONAL			
POMPA DI SCARICO	POMPE DE VIDANGE	DRAIN PUMP	ABLAUFPUMPE	30	30	W
DOSATORE DI LAVAGGIO	DOSEUR DE PRODUIT DE LAVAGE	WASH AID DISPENSER	WASCHMITTELDOSIERANLAGE	OPTION	OPTION	